

Owensboro Grain Company

Technical Data Sheet

Product: Soymax® M113 Soy Wax

Product Code: 170005

DESCRIPTION: Refined, Bleached, and Deodorized Soy Wax

Technical Specifications:

Property	Minimum	Maximum	Method
Mettler Drop Melting Point (°F)	111	115	AOCS Cc 18-80
Color Red (Lovibond)	NA	2.0	AOCS Cc 13j-97
Peroxide Value (meq/kg)	NA	1.5	AOCS Cd 8b-90
Free Fatty Acid (%)	NA	0.2	AOCS Ca 5a-40

Additive: Antioxidants may be added upon customer request.

Application: This 100% fully refined soy wax can be used in a wide range of applications including candle manufacturing, cosmetics, and other.

Availability: Owensboro Grain Co. soy wax is available in dedicated food-grade bulk tanker truck. For samples, pricing, market information, or technical assistance please contact our sales office at the following address:
822 E. 2nd St. Owensboro, KY 42302 1(800)874-0305

Use by date: For optimal quality, it is recommended that a bulk tank of this product be used within 4 weeks of receipt.

Owensboro Grain provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. Owensboro Grain makes no representations or warranties of merchant ability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Owensboro Grain will not be responsible for damages resulting from the use of or reliance upon this information.